

# High Temperature Gas Flares



## landfill systems

engineering a better environment



- Range 10Nm<sup>3</sup>/hr to 2,500Nm<sup>3</sup>/hr
- High temperature combustion (>1,000 °C)
- Fully automated
- Fire safe valves (optional)
- Telemetry & SCADA
- Data logging facility
- Optional control packages
- Energy efficient
- ATEX & DSEAR compliant
- EA compliant

Landfill Systems manufacture two versions of their successful range of High Temperature Gas Flares. These can be used for either de-gassing or power generation applications. Typically, they are the same unit, apart from a two stage fan and a pressure control system that is required for the power generation application.

The flares are fully compliant with the Environment Agency's exhaust emission regulations.

Units are available in a wide range of flow rates from 10Nm<sup>3</sup>/hr up to 2,500Nm<sup>3</sup>/hr.

Training for the safe operation of each flare is provided free of charge at the time of commissioning.

Contact us now for a free no obligation quotation.



For further information contact:

**Landfill Systems**  
**Crowcroft Road Industrial**  
**Estate**  
**Nedging with Naughton**  
**Ipswich**  
**IP7 7HR**



Tel: +44 (0)1449 744475

[michael@landfillsystems.co.uk](mailto:michael@landfillsystems.co.uk)